## **Environics**®

## This "On Demand" gas delivery and gas blending system will provide cost savings and repeatability of your mixture.

The Environics® Series 3000 gas delivery/blending system offers on-site gas blending of 100% pure bulk gases and is configured to provide a solution to using costly premixed cylinders of gas. Unlike premixed cylinders, the Environics model 3000 provides a repeatable blend of gases, using precision thermal mass flow controllers. The system offers flexibility in addressing particular process and market needs. Although two and three gas mixtures are more common, gas mixtures of more constituents can be produced. The primary benefits of the system are cost savings in using pure gases versus premixed cylinders as well as the repeatability of the mixture. The system will undoubtedly pay for itself because of these savings.

The main controls of the system are HMI (Human Machine Interface); color touch screen and PLC combined. A series of I/O modules connect to all the electro-mechanical devices. Ethernet connection comes standard on all S3000. We also provide a free software utility that allows you to remotely monitor and operate the instrument over an Ethernet connection. The system offers options such as remote operation, alarms, a gas humidifier and an oxygen compatible construction.

Precision mass flow controllers (MFC) are used to control the flow rate of each gas for blending. Each MFC is calibrated at 11 points on a primary flow standard traceable to NIST. Using the 11 points of calibration data, the software of the S3000 applies linear interpolation to provide a more accurate and linear flow rate; ultimately providing a precision blend of gases.

Optional precision mass flow meters (MFM) can be installed on the outputs of the MFCs. These electronic meters monitor the flow rate of each flow controller and the PLC mathematically calculates the actual blend concentration based on the metered flows. This provides an independent check on the MFC performance. Each MFM is also calibrated at 11 points with linear interpolation applied.



The system is manufactured in a NEMA 4 wall mount enclosure, with internal electrically grounded aluminum panels for support and a clear polycarbonate door to protect the controls. Optional enclosures are available. Fitting connections and tubing are 316 stainless steel.

When actively mixing, the instrument sends the diluted gas mixture through an in-line static mixer to ensure a homogenous mix of gases. The system provides a controllable positive pressure to meet the requirements of a process downstream. The mixer can be configured to provide gas to a ballast tank, turning off and on as the pressure rises and falls in the tank. This is useful for gas conservation, when the demand for gas is sporadic or intermittent in use.

An optional visual and/or audible alarm can be installed onto the top of the instrument to alert the operator of specific fault conditions. A condition that would trigger an alarm is if the interpreted concentration from the optional flow meters falls outside a user adjustable tolerance.

## **PRODUCT FEATURES AND BENEFITS**

- Optional precision mass flow meters (MFM) can be installed on the outputs of the MFCs.
- Flow standard is accurate up to 1% of reading
- Color touch screen and PLC combined.
- Repeatability up to +/- .05% of fullscale.
- Optional visual and/or audible alarm

## **APPLICATIONS**

- Modified Atmospheric Packaging
- Welding Shielding Gases
- Controlled Atmospheric Storage
- Gas Processing and Blanketing
- Semi-conductor fabrication

Environics<sup>®</sup> and Environics<sup>®</sup> Series 2000 Ultra Clean Computerized Calibration System are trademarks of Environics<sup>®</sup> Inc., 69 Industrial Park Rd East, Tolland, CT 06084. Other trade names or brand names are the property of their respective holders. We hope the information given here will be helpful. It is based on data and knowledge considered to be true and accurate and is offered for the users' consideration, investigation and verification, but we do not warrant the results to be obtained. All specifications and descriptions contained herein are subject to change without notice. Please read all statements, recommendations or suggestions in conjunction with our conditions of sale which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use which would infringe any patent or copyright.

69 Industrial Park Road East, Tolland, CT 06084 (860) 872-1111 Fax: (860) 870-9333 http://www.environics.com E-mail: info@environics.com Copyright 2011 Environics Inc. Printed in USA 4/11